

DATA SHEET

Sinuuous flooring



PRODUCT

Multilayer Oak Parquet with a laminated structure, consisting of a 4mm thick top layer of Oak wood, and a multi-layer plywood support.
 Custom finishes available.

STANDARD MEASUREMENTS

- 2200 X 220 mm
- +Custom size option.

TECHNICAL SPECIFICATIONS

| Wood | Nordic Oak | |
|----------------------------|---------------------------|-------------------------------|
| Total thickness | 15mm thickness | |
| Noble layer thickness | 4mm thickness | |
| Apparent density | +/- 700 kg/m ³ | UNE-EN 323:1994* |
| Moisture content | 7.00 +/- 2 % | UNE-EN 13183-1/AC:2004* |
| Installation | Bonding to substrate | |
| Intended use | Indoor use | |
| Formaldehyde emission | E1 | EN 717* |
| Biological durability | Class E1 | UNE EN 335 -1 ; UNE EN 335-2* |
| Pentachlorophenol emission | < 5 ppm | UNE- EN 14342 |
| Mass per unit area | >500/ m ² | EN 14342* |
| Thermal conductivity | 0.13/0.22 W/M*K | UNE-EN 12667:2002* |
| Thermal resistance | 0.11 M ² *K/W | UNE-EN 12667:2002* |
| Fire reaction | Dfl-s1 | EN 13501* |
| Slip resistance | Class 1 | UNE 41901* |
| Assessment system | Assessment system 4 | |

CERTIFICATION

- Product manufactured according to UNE EN 13489 Standard
- FSC (Forest Stewardship Council) Sustainable Forest Management certification
- Since 1997, TECNALIA quality seal, accredited laboratory by ENAC according to file no. 4/LE024

FEATURES



High-quality product designed for excellent durability.



Material sourced from Europe.



Use of oils and varnishes on wood. This finish preserves the natural appearance of conventional oil while providing increased resistance to everyday stains and requiring less maintenance. Advantages include a natural appearance, low maintenance, and enhanced resistance to water, wine, juice stains, etc.



Oak with a fine brushing, beveled on 4 sides, finished with matte UV varnish. It incorporates two special layers of varnish, one for increased abrasion resistance and the other for greater scratch resistance. The surface is smooth for walnut and merbau.



Suitable for installation over radiant heating and water-based cooling systems.



Emulates the traditional hand-brushed finish of craftsmen from the past, offering a rugged and artisanal look.



Installation system involves gluing the product to the substrate with polyurethane adhesive.



Available without knots or with intermediate knots.



Application of colored oil or varnish on the wood surface to achieve various chromatic ranges.



Structure composed of a top layer showcasing the noble appearance of the material, an intermediate layer of plywood to balance tensions between different parts, and a back layer for counterbalance.



Adhesive application required for installation.